1	EDUCATIONAL OR CONSTRUCTION UNITS	323.06	Piezoelectric element or electrode				
300	NON-DYNAMOELECTRIC	323.07	Oval track				
301	.Nuclear reaction	323.08	Armature				
302	Contact potential difference	323.09	Pressing means detail				
303	P-N semiconductor	323.11	Specific material or				
304	Secondary electron emission		composition				
305	Direct charge particle emission	323.12	Langevin or pencil type				
306	.Thermal or pyromagnetic		motor				
307	With heat actuated bimetal	323.13	Output member detail				
	element	323.14	Roller or ball element				
308	.Charge accumulating	323.15	Material or material				
309	Electrostatic		property				
310	Friction	323.16	Eliptical motion at fixed				
311	.Piezoelectric elements and devices		<pre>point (i.e., walking) or Ratchet and Pawl motor</pre>				
312	Adding or subtracting mass	323.17	Positions an object				
313 R	Surface acoustic wave devices	323.18	Device performs work on an				
313 A	Orientation of piezoelectric		object (e.g., welding,				
313 A	material		cutting)				
313 B	Interdigitated electrodes	323.19	Horn or transmission line				
313 C	Envelope or apodized	323.21	Detector (e.g., sensor)				
313 D	Grating or reflector in wave	324	Diaphragm				
313 2	path	325	Sandwich or Langevin type				
314	Electrical systems	326	Combined with damping structure				
315	Temperature compensation	327	On back of piezoelectric				
	circuits		element				
316.01	Input circuit for simultaneous	328	With mechanical energy coupling				
	electrical and mechanical		means				
	output from piezoelectric	329	Including inertia type				
	element	220	operator				
316.02	Traveling wave motor	330	Bending type				
316.03	Charging and discharging	331	Plural elements				
317	Input circuit for mechanical	332	Multimorph				
	output from piezoelectric	333	Shear or torsional type				
	element	334	Acoustic wave type generator				
318	Input circuit for electrical	335	or receiverWith lens or reflector				
	output from piezoelectric	335					
210	element	337	Nondestructive testing typeUnderwater type				
319	Electrical output circuit	338	Force or pressure measuring				
320	Piezoelectric slab having	330	type				
	different resonant frequencies at different areas	339	Voltage, spark or current				
321	Combined with resonant	337	generator				
321	structure	340	Encapsulated or coated				
322	Acoustic wave type generator	341	With temperature modifier and/				
522	or receiver	312	or gas or vapor atmosphere				
323.01	Direct mechanical coupling		control				
323.02	Motor producing continual	342	For plural piezoelectric				
220.00	motion		elements				
323.03	Traveling wave motor	343	With heating element				
323.04	Stator	344	Sealed unit				
323.05	Support	345	Supported by elastic material				

246	With townships and the	26	Manakaskaiski
346	With temperature compensating	26 27	Magnetostrictive
347	structure	21	Fixed and movable wound elements
	Compensated air gap	20	
348	With mounting or support means	28	Direct-connected
349	Air gap	29	Pivoted or flat-spring
350	Adjustable		armature
351	Suspended by thin member	30	Solenoid and core
352	Point contact on major surfce	31	Self-actuated interrupter
	only	32	Pivoted or flat-spring
353	Contact at edges only		armature
354	Clamped	33	Plural armatures
355	Spring bias	34	Solenoid and core
356	90 degrees to major surface	35	Successively energized
	and margin clamped only		solenoid coils
357	Orientation of piezoelectric	36	.Oscillating
	polarization	37	With motion-converting
358	Ceramic composition (e.g.,		mechanism
	barium titanate)	38	Direct-connected
359	More than one poling	39	With interrupter
	direction (e.g., Rosen	40 R	.Rotary
	transformer)	40.5	Self-nutating or moving (e.g.,
360	Rotation of crystal axis (e.g.,		oscillating fan, etc.)
	cut angle)	41	With mechanical starters
361	Quartz	42	With assembling, metal casting
362	Rochelle salt	12	or machining feature
363	Electrode materials	43	Molded plastic
364	Multilayer	44	Powdered metal
365	Electrode arrangement	45	
366	More than two	46	Impregnated or coated
367			Magnetic motors
368	Piezoelectric element shape	47	Portable or hand tool (e.g.,
	Rectangular plate	4.0	dry shavers)
369	Circular disc, ring, or	48	With other elements
250	cylinder	49 R	Step-by-step
370	"U" or "tuning fork" shape	49 A	Claw-tooth and printed
371	Sphere or hemisphere		circuit components
10	DYNAMOELECTRIC	50	Portable or hand tool
11	.Conducting fluid	51	Vibration or noise suppression
12	.Linear	52	Cooling or fluid contact
13	Fixed and movable wound	53	With control means
	elements	54	Liquid coolant
14	Solenoid and core type	55	Nonatmospheric gas
15	.Reciprocating	56	With gas purification or
16	With cooling or temperature		treating
	modification	57	Intermediate confined coolant
17	With other elements	58	Circulation
19	Speed control or time delay	59	Plural units or plural paths
20	Motion-converting mechanism	60 R	Self-forced
21	Pivoted or flat-spring	61	Rotor passage
	armature	62	Suction pump or fan
22	Plural armatures	63	Pressure pump or fan
23	Solenoid and core type	60 A	Hollow passages
24	Plural cores	64	Heat-exchange structure
25	Reed type	UT	ileat-exchange structure
20	ca c/pc		

6 5	Granaus (a. r. Jaminaa	90.5	Ma ana a bi a la a ani na
65	<pre>Spacers (e.g., laminae, coils, etc.)</pre>	90.5	Magnetic bearing
66	With other elements	92	Supports
67 R	Inbuilt or incorporated unit	92	Torque-transmitting clutches or brakes
67 A	Bicycle-hub generators	93	Brake type
68 R	Electric circuit elements	94	Automatic control
69	Shaft-driven switch (e.g.,	95	By speed
09	blasting generators)	95 96	With other drive mechanism
70 R	Distributor or timer (e.g.,	90 97	Output bias or resistance
70 K	ignition magnetos)	91	device
70 A	Iqnition systems	98	Drive motor
70 A 71	Connectors, terminals or	99	*****
/ 1	lead-ins	100	GearingMechanical clutch
72	Impedance devices	100	Plural units
73	Illuminating devices	101 102 R	
73 68 A	Manually operable (e.g.,	102 R 102 A	Generator-motor type
00 A	switches, rheostats, etc.)		Homopolar clutches
68 B	Condition responsive (e.g.,	103	Magnetic field type
00 Б		104	With air-gap shield
68 C	<pre>position, torque, etc.)Temperature, current-</pre>	105	Induced or eddy current type
00 C		106	Magnetic reluctance feature
68 D	responsive, i.e., protectors	107	With collection means for
۵ م	Conversion elements, (e.g., transformers, rectifiers,	100	induced current
		108	Delivery to external device
68 E	etc.)Motion responsive (e.g.,	109	Electric motor
00 F	_	110	Impedance
74	centrifugal switches)	111	Generated wave-form
7 <del>4</del> 75 R	Inertia or fly-wheel deviceDrive mechanism		modification
75 K 76	Brive mechanism	112	Plural units, structurally
76 77	Brake and clutch		united
		113	Motor-generator sets
78	Clutch	114	Plural rotary elements
79	Shaft and armature timing or	115	Field and armature both rotate
0.0	phasing connection	116	Limited movement
80	Motion conversion	117	Mechanical bias
81	Unbalanced weight (e.g., vibrators)	118	With interconnecting drive
0.0	,		mechanism
82	Swash plate	119	Fluid-drive mechanism
83	Gearing	120	Friction-drive mechanism
84	Impulse coupling	121	Mechanically controlled
75 A	Spring or gravity drive		element
75 B	Hand- or foot-operated	122	By additional
75 C	Rim drive (e.g., bicycle		dynamoelectric machine
	generator drive by wheel, rim,	123	Friction brake
7F 5	or tire)	124	Plural short-circuited rotary
75 D	Flexible shaft or coupling		elements
0.5	and hollow shaft drive	125	Squirrel cage type
85	Mechanical shields or	126	Plural armatures in common
0.6	protectors		field
86	Shield in air gap	127	Plural collector-type machines
87	Submersible	128	Commutator and slip-ring type
88	Dirt, moisture or explosion	129	Synchronous or rotary
0.0	proof		converter
89	Housings, windows or covers	130	For plural wire D.C. system
90	Bearing or air-gap adjustment	131	Different armature circuits
	or bearing lubrication		

122	Dalambana amatana adadina	154 07	77 th
132	Polyphase armature winding	154.27	With an auxiliary pole
133	Common armature winding		extending between stator
134	With plural field windings	154 20	magnet and rotor
135	Commutator in field circuit	154.28 154.29	Specific magnetization
136	Plural commutator type		Specific position or shape
137	Double current D. C. machines	154.31	Single pole pair
138	Dynamotor type	154.32	Permanent magnet extends
139	Hetero-axial excitation	154 00	along an axis
140	Plural armature windings	154.33	Plural rotors
141	Plural field windings	154.34	With adjustable magnetic
142	Plural field windings		structure
143	Plural slip-ring sets	154.35	With specific pole pieces or
144	Plural armature windings		pole shoes
145	Plural sets of poles	154.36	Circumferentially spaced
146	Polyphase windings		poles and magnets
147	Slip rings in field circuit	154.37	Poles extending axially
148	Plural sets of brushes		from magnets
149	Plural field windings	154.38	Pole shoe shape
150	Polyphase arrangement	154.39	Different size
151	Short circuiting conductor	154.41	Laminated
	between brushes	154.42	Induced flux return pole
152	Permanent magnet machines	154.43	Additional permanent magnets
153	Inbuilt with flywheel	154.44	Additional shield or coating
133	(magneto)		(non-magnetic)
154.01	Permanent magnet stator	154.45	Multiple pole pairs
154.02	Combined with generating coil	154.46	With specific pole shoe
154.02	Means for securing magnet		pieces
	Means for securing magnet		
		154.47	_
154.04	Cantilevered	154.47	Magnet extending between two
154.04 154.05	Cantilevered		Magnet extending between two poles
154.04 154.05 154.06	CantileveredAxialPlural sets of magnets	154.48	Magnet extending between two polesInduce flux return pole
154.04 154.05 154.06 154.07	CantileveredAxialPlural sets of magnetsAdhesive	154.48 154.49	Magnet extending between two polesInduce flux return poleAdjustable
154.04 154.05 154.06 154.07 154.08	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yoke	154.48 154.49 155	Magnet extending between two polesInduce flux return poleAdjustableInductor type
154.04 154.05 154.06 154.07 154.08 154.09	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yoke	154.48 154.49 155 156.01	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotor
154.04 154.05 154.06 154.07 154.08 154.09 154.11	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or pole	154.48 154.49 155 156.01 156.02	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse flux
154.04 154.05 154.06 154.07 154.08 154.09 154.11	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holder	154.48 154.49 155 156.01 156.02 156.03	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ring
154.04 154.05 154.06 154.07 154.08 154.09 154.11	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for	154.48 154.49 155 156.01 156.02	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor
154.04 154.05 154.06 154.07 154.08 154.09 154.11 154.12 154.13	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnet	154.48 154.49 155 156.01 156.02 156.03	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust
154.04 154.05 154.06 154.07 154.08 154.09 154.11 154.12 154.13	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clip	154.48 154.49 155 156.01 156.02 156.03 156.04	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearing
154.04 154.05 154.06 154.07 154.08 154.09 154.11 154.12 154.13	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housing	154.48 154.49 155 156.01 156.02 156.03	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor
154.04 154.05 154.06 154.07 154.08 154.09 154.11 154.12 154.13	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clip	154.48 154.49 155 156.01 156.02 156.03 156.04	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for
154.04 154.05 154.06 154.07 154.08 154.09 154.11 154.12 154.13	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housing	154.48 154.49 155 156.01 156.02 156.03 156.04	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or
154.04 154.05 154.06 154.07 154.08 154.09 154.11 154.12 154.13	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnets	154.48 154.49 155 156.01 156.02 156.03 156.04	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging between	154.48 154.49 155 156.01 156.02 156.03 156.04	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for
154.04 154.05 154.06 154.07 154.08 154.09 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedge	154.48 154.49 155 156.01 156.02 156.03 156.04	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensing
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.19	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedge	154.48 154.49 155 156.01 156.02 156.03 156.04	<pre>Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing</pre>
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.19	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet	154.48 154.49 155 156.01 156.02 156.03 156.04 156.05	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnets
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.19	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet characterized by the shape of	154.48 154.49 155 156.01 156.02 156.03 156.04	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnetsMounting (such as on a
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.19 154.21	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet characterized by the shape of the magnet	154.48 154.49 155 156.01 156.02 156.03 156.04 156.05	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnetsMounting (such as on a surface of a shaft)
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.19 154.21	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet characterized by the shape of the magnetWith specific dimension	154.48 154.49 155 156.01 156.02 156.03 156.04 156.05	<pre>Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnetsMounting (such as on a surface of a shaft)Keyed to shaft</pre>
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.19 154.21	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet characterized by the shape of the magnetWith specific dimensionHorseshoe	154.48 154.49 155 156.01 156.02 156.03 156.04 156.05	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnetsMounting (such as on a surface of a shaft)Keyed to shaftMagnets in shaft
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.19 154.21	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet characterized by the shape of the magnetWith specific dimensionHorseshoeBar, square or rectangular	154.48 154.49 155 156.01 156.02 156.03 156.04 156.05	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnetsMounting (such as on a surface of a shaft)Keyed to shaftMagnets in shaftMounted on a sleeve/hub
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.21	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet characterized by the shape of the magnetWith specific dimensionHorseshoeBar, square or rectangularDisk, ring, or cylinder	154.48 154.49 155 156.01 156.02 156.03 156.04 156.05	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnetsMounting (such as on a surface of a shaft)Keyed to shaftMagnets in shaftMounted on a sleeve/hubKeyed to a sleeve/hub
154.04 154.05 154.06 154.07 154.08 154.11 154.12 154.13 154.14 154.15 154.16 154.17 154.18 154.21	CantileveredAxialPlural sets of magnetsAdhesiveMounted to magnet yokeSplit housing/yokeEmbedded in core or poleCylindrical sleeve holderHolder with pocket for magnetSpring clipClip secured to housingAxially pressing on magnetsWedging betweenWith a magnetic wedgeWith an integral wedgePermanent magnet characterized by the shape of the magnetWith specific dimensionHorseshoeBar, square or rectangularDisk, ring, or cylinderWith means to prevent or	154.48 154.49 155 156.01 156.02 156.03 156.04 156.05	Magnet extending between two polesInduce flux return poleAdjustableInductor typePermanent magnet rotorTransverse fluxWith a hysteresis ringSeparate portion of the rotor magnet used as a thrust bearingSeparate portion of the rotor magnet used as a magnet for sensing (i.e., for position or frequency)Combined with flux for sensingAdditional flux directing magnetsMounting (such as on a surface of a shaft)Keyed to shaftMagnets in shaftMounted on a sleeve/hub

156.15	Induced flux pole on sleeve/hub	156.57	With slots or holes to guide flux
156.16	Spring mounted	156.58	Different size pole shoes
156.17	Spring mounted flux shunt	156.59	Pole shoes fixed to hub or
156.18	With a threaded fastener		shaft.
156.19	With a wedge	156.61	Pole shoes fixed with end
156.21	With an adhesive	130.01	plates
156.22	With an axial end clamp	156.62	Axially magnetized with
156.23	With casting material around	130.02	poles shoes at one end
150.25	_	156.63	Laminated pole shoes
156 04	the magnet	156.64	
156.24	Including a spring mount to	130.04	Axially magnetized with pole shoes at both ends
156 05	adjust a flux	156 65	
156.25	Axially offset and radially	156.65	Laminated pole shoes
	magnetized magnets	156.66	Claw poles/interfitting
156.26	Mounted on a bell shape hub	156 65	poles/lundel
156.27	Including thermal	156.67	Laminated pole shoes
	compensation	156.68	Poles formed by magnet
156.28	Sleeve covering magnet face	156.69	Plural sets of claw poles
156.29	Sleeve parallel to magnetic	156.71	Claw poles extend in the
	face		same axial direction
156.31	Banding around magnet	156.72	Additional support for
156.32	Including an axial air gap		magnet
156.33	With pole shoes	156.73	Additional support for claw
156.34	With a stator between a		pole tips
	rotating flux return plate and	156.74	Damping features
	rotor magnet	156.75	Damper plate on magnetic
156.35	With single rotor magnet and		face
	plural stators	156.76	Damper in pole pieces
156.36	With plural sets of rotating	156.77	Damper cage around magnet
	magnets	156.78	Squirrel cage
156.37	With single stator and	156.79	Including laminated ring
	plural sets of rotating	156.81	Magnet positioned between
	magnets		squirrel cage and stator
156.38	Specific shape	156.82	Axially magnetized magnets
156.39	Horseshoe		or axially positioned magnets
156.41	Triangular	156.83	Including a flux barrier
156.42	Star	156.84	Flux barrier is a magnet
156.43	Specific magnetization	157	Vertically disposed
	Different pole width	158	Universal (A.C. or D.C.)
156.45	Specific dimensions	159	
156.46	Shaped to vary air		A.C.
		160	Frequency converters
156.47	Skewed	161	Phase-shifter type
156.48	Pole shoes/pole pieces	162	Synchronous
156.49	Radial flux path and	163	Reaction type
	radially positioned pole shoes	164	Toroidal coil
156.51	Laminated pole shoes with	165	D.C. excited
	multiple pole pairs	166	Induction
156.52	Laminated pole shoes with	167	With repulsion-starting
	single pole pair	168	Inductor-type generators
156.53	Embedded in a core		(variable reluctance)
156.54	Induced flux return poles	169	High frequency
156.55	Circumferential flux path	170	Multifrequency
	and circumferential pole shoes	171	Induction generators
156.56	Embedded		

172	Shifting field (e.g., shading	212	Inherently variable
	pole)		impedance (double squirrel
173	Commutated		cage)
174	Single phase	213	Antiparasitic conductors
175	Conduction operation		(imbricated)
176	Transformer operation	214	Coil retainers or slot closers
177	D.C.	215	Slot liners
178	Homopolar	216	Core features
179	_	217	Securing laminae
	Windings and core structure	217	_
180	Field or excitation windings or structure	210	Pole assembly and securing means
181	Combined permanent and	219	Current collectors
	electromagnet	220	Spark-reduction
182	With short-circuited winding	221	Arc extinguishers
-	or conductor	222	Spark-neutralizing current
183	Damper winding	223	Flux compensators
184	Plural field windings	224	Commutating poles or
185	Plural sets of poles	221	windings
186		225	Short-circuited coil circuit
100	Interpole, compensating or	225	
100	neutralizing poles		Field-distortion
187	Slotted or divided pole	227	With cooling
188	Differentially related	228	With cleaning, lubricating,
189	Variable length or tapped winding	229	resurfacing or repairingBrush-traversing
190	Magnetic shunts for shifting	230	Circumferential brush shifting
100	field flux	230	on reversal
191	Adjustable magnetic structure	231	Rotary structure
192	Nonmagnetic inserts or air	232	Slip rings
	gaps	233	Commutators
193	Nonuniform core cross section	234	Winding connectors
194	Coil supports and spools	235	Molded support
195	Armature or primary	236	Cylindrical or drum
196		237	Disc
	Corona-prevention	_	
197	With short-circuited winding	238	Fixed structure
	or conductor	239	Brush holders or rigging
198	Plural windings	240	Brush-lifting
199	Combined stationary and	241	Circumferential adjustment
	rotary	242	Brush engagements or guides
200	Variable length or tapped	243	Fluid pressure-operated
	windings	244	Brush affixed to pivoted arm
201	Bar windings	245	Slidable brush
202	Open windings	246	Pressure arm
203	Closed windings	247	Axial spring
204	Equalizers	248	Brushes
205	Multiplex	249	With electrical connector
206	Lap	251	Structure (e.g., composite
207	Wave	231	
	Coils	252	material)
208		252	With composition feature
209	Adjustable magnetic structure	253	Carbonaceous
210	Secondary windings or	254	Stator structure
011	conductors	255	For railway-type machines
211	Squirrel cage	256	Stray field flux loss prevention

257	Interfitting or claw-tooth stators	DIG 3	В на	LL EFFECT	GENERATORS	AND
258	Frame and core type	DIG 6	PR	INTED-CIR	CUIT MOTORS	AND
259	Core assembly			COMPONENT	rs	
260	End turn supports					
261	Rotor structure					
262	High-speed rotor type					
263	Interfitting or claw tooth					
	rotors					
264	Armatures					
265	Drum					
266	Hollow (e.g., double air gap)					
267	Ring					
268	Disc					
269	Salient pole					
270	End turn supports					
271	Banding					
272	Elements					
273	Miscellaneous					
40 MM	Miniature motors					

#### CROSS-REFERENCE ART COLLECTIONS

800 PIEZOELECTRIC POLYMERS (E.G., MYLAR, PVDF)

## FOREIGN ART COLLECTIONS

# FOR 000 CLASS-RELATED FOREIGN DOCUMENTS

Any foreign patents or non-patent literature from subclasses that have been reclassified have been transferred directly to FOR Collections listed below. These Collections contain ONLY foreign patents or non-patent literature. The parenthetical references in the Collection titles refer to the abolished subclasses from which these Collections were derived.

FOR 100 PERMANENT MAGNET STATOR (310/154) FOR 101 PERMANENT MAGNET ROTOR (310/156)

### **DIGESTS**

### DIG 2 HYSTERESIS ROTORS AND MOTORS